

# **Quick Start Guide:** Statesman Portable Toilet

# I To Set Up:

### 1. Fill up the fresh water tank with water.

To access the fresh water tank, simply unscrew the Filler Cap next to the basin and add water through a garden hose. The water will be used for flushing the toilet and washing your hands.

Note: To drain the water tank, simply unscrew the Drain Plug found underneath the basin (above the small foot pump).



#### 2. Place some water in the waste tank.

To access the waste tank, simply lift the toilet bowl and add in 10-20 litres of water through a garden hose or bucket. The water will help to break down and liquify the waste.



#### 3. Throw in some deodorisers.

Add a Deodoriser Tablet to the waste tank to neutralize any odours. For ongoing maintenance, repeat this step every 1-2 weeks.





# **Quick Start Guide:** Statesman Portable Toilet

## **To Service:**

## If you DO NOT have a Rear Waste Valve:

1. Your toilet will need to be serviced by a liquid waste management company. A liquid waste management company will remove the waste by lifting the toilet bowl and using a vacuum hose.

## If you DO have a Rear Waste Valve:

Note: If you have a Rear Waste Valve, you will also need a Type D Alloy 75mm Female Camlock x 75mm Female NPT Thread AND a 3m Lay Flat Hose with 3" Male Camlock Fitting.

- 1. To service the toilet, screw the Type D Camlock onto the Rear Waste Valve and hook the hose up.
- 2. To open the Rear Waste Valve, lift upwards on the handle.
- 3. Once the Rear Waste Valve is opened, gravity will feed the waste out from the waste tank. It is important to keep the toilet slightly elevated during this process.
- 4. Once the waste has been removed, lift the toilet bowl up and either use a garden hose or buckets of water to flush out any excess waste.





## Got questions or need help?

Contact us at 1800 POO WEE or email sales@portabletoilets.com.au

Australian Portable Toilets CALL 1800 POO WEE (1800 766 933)